



COUGAR 8942 HAMMER AND CHISEL PASTE

FEATURES & BENEFITS

- Fortified with copper and graphite.
- Excellent load and shock load resistance properties. Weld point score of 800.
- Calcium sulfonate complex thickener.
- Heavy duty ISO 460 base oil.
- Inherently adhesive.

Cougar 8942 Hammer & Chisel Paste has been especially designed to provide high performance lubrication of hydraulic hammers. It is manufactured from a Calcium Sulfonate complex thickener, containing more than 10% of copper and graphite solids which provide excellent high temperature, extreme pressure, and heavy load carrying capabilities.

Cougar 8942 Hammer & Chisel Paste also features the maximum 800 weld point score on the four ball EP (Extreme Pressure) test, one of the highest quality hydraulic hammer/breaker lubricants available.

Cougar 8942 is recommended for the greasing of the tool and bushings on hydraulic hammers and breakers to prevent wear and extend life of the tool and meets all OEM requirements for hydraulic hammer and hydraulic breaker lubrication.

TYPICAL CHARACTERISTICS

Grade CG	8942
Colour	Copper / Grey
Thickener Type	Calcium Sulfonate Complex
NLGI Grade	2
Dropping Point, min D 2265	300°C
4-Ball EP, weld point D 2596	800 kg
4-Ball Wear, Scar Dia, mm D 2266	0.39
Corrosion Prevention D 1743	PASS
Solids, Graphite & Copper	14 %
Base Oil Viscosity @ 40°C, cSt	460
Viscosity Index	95
Dry Film Lubrication	980 °C
Temperature Range	-15°C to 180 °C Short Periods 200°C